

HINGED GRATE
AND FRAME

Delta 40



PATENTED MODEL

DIMENSIONS

REFERENCE		A x B Ext. frame length	H Depth	C x D Grate length	P x P1 Clear opening	CHARACTERISTICS	WATERWAY AREA dm ²	UNITS PER PALETTE
DELTA 40	R0740	430 x 275	40	390 x 225	350 x 200	Hinged-ANTIVANDAL-PROOF Ductile Iron	5	200
DELTA 45	R0745	500 x 305	35	455 x 265	425 x 230		8	150
DELTA 50	R0766	625 x 395	40	565 x 300	530 x 265	Hinged ANTIVANDAL-PROOF Ductile Iron	14	80
DELTA 50V	R0766V	620 x 390	70	565 x 300	530 x 265	Ductile Iron C-250	14	20
DELTA 75	R0775	790 x 335	40	745 x 250	720 x 270	Hinged-ANTIVANDAL-PROOF Ductile Iron	12	30
DELTA 80	R0785	910 x 365	100	740 x 275	715 x 240	Hinged-ANTIVANDAL-PROOF Ductile Iron C-250	12	30

CHARACTERISTICS

Made of ductile iron. Fulfils the requirements of European standards EN-124.

R0745, R0766, R0766V and R0785 grates, C-250 class.

Ductile iron grate formed by diagonal bars that guarantee the maximum water collection and avoid bicycles to get blocked with it.

Black paint coating.

Slip-proof surface.

